### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

- (Original) A method of multi-mode communications, the method comprising:
  receiving signals from multiple sources at a plurality of sample buffers;
  referencing the plurality of sample buffers for a first source at one time and referencing the plurality of sample buffers for a second source at another time; and communicating data from the referenced plurality of sample buffers to a processing unit, wherein the processing unit concurrently receives inputs from buffers in the plurality of sample buffers and outputs to other buffers in the plurality of sample buffers.
- (Original) The method of claim 1, wherein samples from the first source are demodulated and samples from the second source are not demodulated.
- 3. (Original) The method of claim 1, wherein samples from the first source are demodulated and samples from the second source are partially processed.
- (Original) The method of claim 1, wherein the multiple sources comprise communication sources operating using different communication protocols.
- (Original) The method of claim 1, wherein the different communication protocols comprise any one of CDMA technologies, OFDM technologies, 802.11a, 802.11b, and 802.11g.
- 6. (Original) The method of claim 1, wherein the multiple sources comprise multiple communication receivers.
- (Canceled).
- (Currently Amended) <u>A method of multi-mode digital communications, the [[The]]</u> method of claim 7, further comprising:

asynchronously processing received communication samples at a processing unit, wherein the communication samples processed by the processing unit

## correspond to more than one communication protocol specification;

# controlling the processing unit by programmed instructions; and

updating the programmed instructions based on processing factors.

- (Original) The method of claim 8, wherein the processing factors comprise any one of processing results, user preferences, and system information.
- 10. (Original) The method of claim 8, wherein updating the programmed instructions comprise instructions to implement a new communication protocol specification.
- 11. (Currently Amended) <u>A method of multi-mode digital communications, the [[The]]</u> method of elaim 7, further comprising:

# asynchronously processing received communication samples at a processing unit, wherein the communication samples processed by the processing unit correspond to more than one communication protocol specification:

## controlling the processing unit by programmed instructions; and

selectively directing the communication samples from separate buffers to one processing unit of a plurality of processing units.

12. (Original) A system for multi-mode communications, the system comprising: means for receiving signals from multiple sources at a plurality of sample buffers:

means for referencing the plurality of sample buffers for a first source at one time and referencing the plurality of sample buffers for a second source at another time; and means for communicating data from the referenced plurality of sample buffers to a processing unit, wherein the processing unit concurrently receives inputs from buffers in the plurality of sample buffers and outputs to other buffers in the plurality of sample buffers.

- 13. (Original) The system of claim 12, wherein samples from the first source are demodulated and samples from the second source are not demodulated.
- 14. (Original) The system of claim 12, wherein samples from the first source are demodulated and samples from the second source are partially processed.

- 15. (Original) The system of claim 12, wherein the multiple sources comprise communication sources operating using different communication protocols.
- (Original) The system of claim 12, wherein the different communication protocols comprise any one of CDMA, 802.11a, 802.11b, and 802.11g.
- 17. (Original) The system of claim 12, further comprising means for selectively directing data from separate buffers to one processing unit of a plurality of processing units.
- 18. (Original) The system of claim 12, further comprising means for selectively directing data from separate buffers to one processing unit of a plurality of processing units, wherein the one processing unit is configured to perform vector processing operations.
- (Original) The system of claim 18, further comprising means for accumulating results of successive outputs.
- 20. (Original) The system of claim 18, wherein the vector processing operations comprise a single instruction that drives calculation of a vector.